QTE TECHNOLOGIES

0 | USD

Search products, manufacturers and suppliers...

Home / News / Everything About Solar Panel - Types, Working and Every Other Features in Details

EVERYTHING ABOUT SOLAR PANEL - TYPES, WORKING AND EVERY OTHER FEATURES IN DETAILS

07/26/25 09:22:00 PM

Solar panels, also known as photovoltaic (PV) modules, convert sunlight into direct current (DC) electricity by harnessing the photovoltaic effect. They form the core of solar power systems—from small off-grid setups to utility-scale solar farms—and play a pivotal role in the global transition to clean energy.

1. Photovoltaic Working Principle

The photovoltaic effect is the process by which certain semiconductor materials generate electric current when exposed to light.

- Sunlight carries photons that strike a PV cell's semiconductor layers.
- Each photon with sufficient energy liberates an electron, creating an electron–hole pair.
- An internal electric field at the p-n junction drives freed electrons toward the negative side, producing DC current.
- Metal contacts on the cell collect this current and route it to the module's junction box.

2. Core Structural Components

A standard crystalline-silicon solar panel comprises multiple layers designed for durability and optimal light harvesting:

- Tempered glass frontsheet: high light transmission and impact resistance.
- Encapsulant (EVA): cushions cells and blocks moisture ingress.
- PV cells: monocrystalline or polycrystalline silicon wafers.
- Backsheet: multi-layer polymer that provides electrical insulation and UV protection.
- Aluminum frame: supports and secures the module.
- Junction box with bypass and blocking diodes: ensures safe current flow and minimizes hotspot damage.

3. Classification of Solar Panels

3.1 By Cell Material and Technology

- Monocrystalline Silicon • Made from single-crystal ingots cut into wafers. • High efficiencies (20–25%), sleek black appearance, long life (30–40 years).
- Polycrystalline Silicon • Cast from multiple silicon crystals; recognizable blue hue. • Moderate efficiencies (15–18%), lower cost, shorter lifespan than mono-Si.
- Thin-Film Technologies • Includes cadmium telluride (CdTe), copper indium gallium selenide (CIGS), and amorphous silicon (a-Si). • Flexible, lightweight modules; efficiencies of 10–18%; best for curved surfaces and building-integrated PV.
- Passivated Emitter and Rear Cell (PERC) • Rear-surface passivation layer reflects unabsorbed photons back into the cell, boosting efficiency by 1–2 % over standard mono-Si.
- Tunnel Oxide Passivated Contact (TOPCon) and Heterojunction (HJT) • TOPCon cells feature an ultrathin oxide and conductive contact on the rear, reducing recombination. • HJT combines crystalline Si with amorphous Si layers, achieving >24 % lab efficiencies and excellent temperature response.
- Bifacial Panels • Transparent backsheet or dual-glass design captures albedo light from the rear side, increasing energy yield by 5–30 % under reflective conditions.
- Emerging Perovskite and Tandem Cells • Perovskite materials show rapid efficiency gains (>25 %) at lower manufacturing costs; tandem perovskite/Si cells aim for 30 %+ practical efficiencies.

3.2 By System Configuration

- Grid-Tied Modules: no battery needed; excess power can feed into the utility grid.
- Off-Grid Modules: paired with battery storage for complete energy independence.
- Hybrid Modules: connect to both grid and batteries, optimizing self-consumption and backup power.

4. Key Technical Specifications

Parameter	Unit	Description
Maximum Power (Pmax)	W (Wp)	Peak output at Standard Test Conditions (1000 W/m², 25 °C)
Open-Circuit Voltage (Voc)	V	Voltage when no load is connected
Short-Circuit Current (Isc)	A	Current when output terminals are shorted
Voltage at Pmax (Vmpp)	V	Operating voltage at maximum power point
Current at Pmax (Impp)	A	Operating current at maximum power point
Temperature Coefficient	%/°C	Power loss per °C rise above 25 °C
Annual Degradation Rate	%/year	Yearly decline in Pmax, typically 0.5–0.7 %
Load Rating	Pa/kg m²	Mechanical resistance to snow and wind loads
Ingress Protection (IP)	–	Dust and water resistance rating of the module

5. Advanced Features and Innovations

- Half-Cell and Multi-Busbar Designs • Splitting cells reduces resistive losses; more busbars shorten electron pathways.
- Smart Modules and Integrated Electronics • Embedded microinverters or power optimizers for module-level maximum power point tracking (MPPT) and shade mitigation.
- Tracking Systems • Single- and dual-axis trackers tilt panels toward the sun, boosting annual yield by 10–30 %.
- Agrivoltaics (Agri-PV) • Elevated bifacial arrays provide crop shading while generating power.
- Building-Integrated PV (BIPV) • Solar roof tiles, façade panels, and translucent modules that replace conventional building materials.

6. Installation, Operation, and Maintenance

- Optimal Tilt and Orientation • Tilt angle ≈ latitude ±10°; south-facing in the Northern Hemisphere maximizes year-round exposure.
- Mounting Systems and Wind/Snow Loads • Racking must conform to local building codes and load requirements.
- Cleaning, Inspection, and Monitoring • Quarterly visual checks and annual infrared scans to detect hotspots. • Automated cleaning robots for large ground-mount installations. • Online monitoring platforms track power generation and alert on performance deviations.

7. Performance Longevity and Warranties

- Product Warranty: 10–15 years covering material defects and workmanship.
- Performance Warranty: guarantees ≥ 80 % of nominal Pmax after 25 years.
- Typical annual degradation rates: 0.3–0.7 %, with premium modules at the low end.

8. Future Trends in Solar Technology

- Tandem Perovskite/Silicon Cells Approaching 30 %+ Efficiency.
- Flexible and Semi-Transparent PV for Windows and Wearable Electronics.
- AI-Driven MPPT Algorithms and Predictive Maintenance.
- 3D-Printed Interconnects and Nano-Textured Surfaces for Enhanced Light Trapping.
- Fully Automated, Robotic Installation and Cleaning Systems for Utility-Scale Parks.

Harnessing solar energy effectively requires deep understanding of panel types, construction details, electrical behavior, and maintenance practices. By selecting the appropriate technology—be it high-efficiency monocrystalline modules, cost-effective thin-film solutions, or cutting-edge tandem cells—you can tailor a solar installation that maximizes yield, reliability, and return on investment. With continuous innovation on the horizon, solar photovoltaics will remain at the forefront of sustainable energy solutions.

To buy solar panels at the best prices, visit QTE Technologies. QTE Technologies is a proud global MRO provider, serving customers in over 180 countries. Established in 2010, we supply over 1 million products across every industry and technology. Additionally, you can reach us anytime via 24×7 chat support, phone, WhatsApp or email. Discover what our valued customers have to say about our services on our dedicated review page.

Post Author By QTE Technologies Editorial Staff (with a solid background in both technical and creative writing - accumulated 15+ years of experience).

FEATURED NEWS

How Industry 4.0 is Making a Positive Change to Industrial Manufacturing?

07/25/25

How Electronic Procurement Helps Businesses Gain a Competitive Advantage

04/21/25

Looking for investors

04/18/23

WAREHOUSE OPERATION AND MANAGEMENT WITH ROBOT & AI CREATIVE INTELLIGENCE

01/02/21

Sign up for the newsletter - the opportunity to receive promotions

Enter the email to receive news...

Sign up for the newsletter »

QTE TECHNOLOGIES CO.,LTD

Head Office

Address: 11th Floor, Zen Tower, No.12 Khuat Duy Tien St, Thanh Xuan Ward, Hanoi, Vietnam

Phone: +84 935 486 698

Hotline: +84 935 486 698

Email: info@qtetech.com.vn

Website: https://qtetech.com/

Transaction office in Ho Chi Minh City

Address: 18th Floor - Indochina Park Tower - 04 Nguyen Dinh Chieu St, Tan Dinh Ward, Ho Chi Minh City, VietNam

Phone: +84 935 486 698

Hotline: +84 935 486 698

Email: info@qtetech.com.vn

Website: https://qtetech.com/

Transaction office in Da Nang

Address: 9th Floor - Lighthouse Building - No.1254 Xo Viet Nghe Tinh - Hoa Cuong Ward - Da Nang City - Vietnam

Phone: +84 935 486 698

Hotline: +84 935 486 698

Email: info@qtetech.com.vn

Website: https://qtetech.com/

CONNECT WITH US

LINK

- About
- Catalog
- Ordering guide
- Payment guide
- Privacy Policy
- Return Policy
- Shipping Policy
- Warranty Policy
- Complaint settlement policy
- Policy with the manufacturer
- Recruitment
- Contact us
- Tax / Duty (Duties)
- Compliance/ Export Control
- Help Center/ Terms and Conditions
- FAQ

ĐÃ THÔNG BÁO
BỘ CÔNG THƯƠNG